


## DETAIL B ELECTROLIER ANCHOR BOLTS

ANCHOR BOLTS

## NOTES:


- I. Anchor bolt or stud length shall be such that thread extends 13 mm ( $\frac{1}{2}$ ") maximum above nut on level base plate after grouting. See Detail "N".
- 2. Electrolier anchor bolts shall be held in position for pouring by means of anchor plates and suitable templates. Deviation from the true position, vertical and height, shall not exceed L5 mm (1/46").
- 3. See railing sheets for reinforcement and structural details at electroliers and pull boxes.



34

Туре	Bolt Circle	Anchor Bolt Diameter
15	280 mm (II")	25 mm (I")
21	305 mm (I2")	32 mm (l <sup>1</sup> / <sub>4</sub> ")

ANCHOR PLATE



DETAIL N GROUTING AT ELECTROLIER

> STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION

## LIGHTING STANDARDS TYPES 15 AND 21 BARRIER RAIL MOUNTED DETAILS

These "Standard Plans for Construction of Local Streets and Roads" contain units in two systems of measurement: International System of Units (SI or "metric") and United States Standard Measures shown in the parentheses (). The measurements expressed in the two systems are not necessarily equal or interchangeable. See the "Foreword" at the beginning of this publication.

NO SCALE

ES-6B